

Digitale manometers

TYPE: ETD-10, klasse 1.0
KASTDIAMETER: 66 MM
Bereiken: -1 - 0 tot 0 - 250 bar
Nauwkeurigheid: 1,0%
Aansluiting: 1/4" BSP
Drukeenheid: Bar, KPa, PSI, KG/cm³, MPA
Batterij: 2x 1.5V, AAA. Duur > 2400 uur
Display: 3-cijferig LCD display



Specificaties

Auto-zero.
Achtergrond licht wit.
Behuizing RVS 304. Aansluiting RVS 304.

909001	99,00	-1 - 0
909002	99,00	0 - 1.6
909003	99,00	0 - 2.5
909004	99,00	0 - 4
909005	99,00	0 - 6
909010	99,00	0 - 10
909016	99,00	0 - 16
909025	99,00	0 - 25
909040	99,00	0 - 40
909060	99,00	0 - 60
909100	99,00	0 - 100
909160	99,00	0 - 160
909250	99,00	0 - 250
909000	8,50	beschermkap/IP65

Digitale Manometer - Type ETD-10 / Bladzijde 2

Overload capacity	<100 bar 200%; > 100 bar 150%
Backlight	Yes
Size	66 mm
Accuracy	1% FS
Working temperature	-10 – 70 °C
Environment temperature	18 ~ 30 °C
Electromagnetic compatibility	EN61326
Measuring rate	2/sec
Measurement medium	Gas/water/oil
Connection standard	¼" BSP, on request: M10x1, ¼" NPT
Connection material	304SS (1.4301)
Case	304SS (1.4301)
Batteries	2x Mignon AAA (included)
Battery lifetime	2400 hours
Weight	0,3 KG

Afmetingen

