

## Digitale manometers

**TYPE:** ETD-11, klasse 0.4  
**KASTDIAMETER:** 80 MM  
 Bereiken: -1 - 0 tot 0 - 600 in Bar  
 0 - 50 tot 0 - 500 in Mbar  
 Nauwkeurigheid: 0,4%  
 Aansluiting: 1/4" BSP  
 Drukeenheid: Bar, KPa, PSI, KG/cm2, MPA  
 Batterij: 2x 1.5V, AA. Duur > 12 maanden  
 Display: 4-cijferig LCD display



## Specificaties

Auto-zero. Achtergrond licht wit.  
 Min/Max-geheugen. Grafische lijn weergave van 0 tot 100%.  
 Behuizing RVS 304. Aansluiting RVS 304.

COMPLEET OVERZICHT TECHNISCHE INFORMATIE ZIE VOLGENDE BLADZIJDE

| Bestelcode | Prijs € | Aanwijzing: bar  |
|------------|---------|------------------|
| 919001     | 159,00  | -1 - 0           |
| 919002     | 149,00  | 0 - 1            |
| 919003     | 149,00  | 0 - 1.6          |
| 919004     | 149,00  | 0 - 2.5          |
| 919005     | 149,00  | 0 - 4            |
| 919006     | 149,00  | 0 - 6            |
| 919010     | 149,00  | 0 - 10           |
| 919016     | 149,00  | 0 - 16           |
| 919025     | 149,00  | 0 - 25           |
| 919040     | 149,00  | 0 - 40           |
| 919060     | 149,00  | 0 - 60           |
| 919100     | 149,00  | 0 - 100          |
| 919160     | 149,00  | 0 - 160          |
| 919250     | 149,00  | 0 - 250          |
| 919400     | 149,00  | 0 - 400          |
| 919600     | 159,00  | 0 - 600          |
| 919201     | 179,00  | 0 - 50 Mbar      |
| 919202     | 179,00  | 0 - 100 Mbar     |
| 919203     | 179,00  | 0 - 250 Mbar     |
| 919204     | 179,00  | 0 - 500 Mbar     |
| 919000     | 9,50    | beschermkap/IP65 |

## Digitale Manometer - Type ETD-11 / Bladzijde 2

|                               |  |
|-------------------------------|--|
| Overload capacity             | <40 bar 150%; > 40 bar 120%                                |
| Backlight                     | Yes  |
| Size                          | 88 mm  |
| Accuracy                      | 0,4% FS, optional 0,2% FS                                  |
| Working temperature           | -10 – 60 °C  |
| Environment temperature       | 0 ~ 40 °C  |
| Electromagnetic compatibility | EN61326  |
| Measuring rate                | 3/sec  |
| Measurement medium            | Gas/water/oil  |
| Connection standard           | C" BSP, on request: M10x1, ¼" NPT, ½" BSP, ½" NPT, M20x1,5 |
| Connection material           | 304SS (1.4301)   |
| Case                          | 304SS (1.4301)   |
| Batteries                     | 2x Mignon AAA (included)                                   |
| Battery lifetime              | 12 months  |
| Weight                        | 0,35 KG  |

### Afmetingen

