



## Polyester Polyurethane PUR-DUO hoses

### Temperature range

-35 °C to +60 °C

**PUR hoses** are welded together to form hose groups. For the installation, the hose group is separated at both ends to the desired length.

**Note:** Use exclusively in combination with union nuts.

### Can be delivered ex warehouse

Roll length: 50 m

### Colour (abbreviation)

We deliver PUR-DUO hoses in:

DUO hoses  
blue / black  
(bl / sw)

TRIO hoses  
blue / black / natural  
(bl / sw / nf)

QUATRO hoses  
blue / black / natural / green  
(bl / sw / nf / gn)

### Nominal dimensions

AD = outer diameter  
ID = inner diameter  
(Production dimension)  
Wall thickness

### Tolerances

See page A 36



## Polyester Polyurethane PUR-DUO hoses ●

Product No.	Type	Nominal dimensions		Wall thick- ness mm	Colour	Op. pressure 20 °C bar	Min. bending radius mm	Weight g/m
		AD mm	ID mm					
3553	PUR-DUO	4	2	1	bl / sw	21	10	23.0
3554	PUR-DUO	4.3	3 (2.9)	0.70	bl / sw	12	14	19.4
35541	PUR-DUO	5	3	1	bl / sw	16	12	30.6
3555	PUR-DUO	6	4 (3.9)	1.05	bl / sw	14	20	42.8
3556	PUR-DUO	8	6 (5.7)	1.15	bl / sw	12	35	60.4
3557	PUR-DUO	10	8 (7.7)	1.15	bl / sw	9	60	78.0