



## Polyether Polyurethane PUR-DUO hoses of type 1154

### Temperature range

-25 °C to +50 °C

**PUR hoses** are welded together to form hose groups. For the installation, the hose group is separated at both ends to the desired length.

**Note:** Use exclusively in combination with union nuts.

### Available upon request

Roll length: 50 m

### Colour (abbreviation)

We deliver PUR-DUO hoses in:

DUO hoses  
blue / black transparent  
(bl-tp / sw-tp)

### Nominal dimensions

AD = outer diameter  
ID = inner diameter  
(Production dimension)  
Wall thickness

### Tolerances

See page A 36



## Polyether Polyurethane PUR-DUO hoses of type 1154 ●

Product No.	Type	Nominal dimensions		Wall thickness mm	Colour	Op. pressure 20 °C bar	Min. bending radius mm	Weight g/m
		AD mm	ID mm					
3580*	PUR-DUO	4	2	1	bl/sw transparent	25	10	22.0
3581*	PUR-DUO	6	4 (3.9)	1.05	bl/sw transparent	15	20	38.2
3582*	PUR-DUO	8	6 (5.7)	1.15	bl/sw transparent	11	35	57.9
3583*	PUR-DUO	10	8 (7.7)	1.15	bl/sw transparent	8	55	74.8